

## Storage Shed

### SHED Lumber

- Framing:
- ▲ (44) 2" x 4" - 8'
  - ▲ (11) 2" x 4" - 10'
  - ▲ (5) 2" x 4" - 12'
- Ridge Beam:
- ▲ (1) 2" x 6" - 14'
- Door Trim:
- ▲ (1) 1" x 4" - 8"
  - ▲ (4) 1" x 4" - 10'
- Doorway and Gable End Batten:
- ▲ (8) 1" x 4" - 8"
  - ▲ (2) 1" x 4" - 6'

### Batten Trim:

- ▲ (2) 1" x 4" - 10'
  - ▲ (2) 1" x 4" - 12'
  - ▲ (36) 1" x 4" - 8'
- Wall, Roof, Door and Gable End Covering:
- 20 sheets 4' x 8' x 1/2" Exterior Plywood

### Hardware and Other Materials


- ▲ 3d, 6d, 10d and 20d Nails as required
- ▲ Steel 'T' Door Hinges: 3 pr.
- ▲ Safety Hasp: 1 pc.
- ▲ Shingles: Sufficient amount for 170 sq. ft. Roof Area plus 13 ft. of Ridge and 26 ft. of Eaves

- ▲ Asphalt Roofing Paper: 2 rolls
- ▲ 7/16" Roofing Nails as required

### FLOOR Lumber

- ▲ (12) 4" x 4" - 4' Main Support Posts (length may vary according to terrain)
- ▲ (4) 2" x 8" - 12' Header Boards
- ▲ (2) 2" x 8" - 12' Fascia Ribbon Boards
- ▲ (2) 2" x 8" - 10' Fascia Ribbon Boards
- ▲ (8) 2" x 8" - 10' Joists
- ▲ (22) 5/4" x 6" - 12' Floor Decking


**Doors**  
Cut Double Doors from 2 sheets of 1/2" Wolmanized plywood and attach 1" x 4" Wolmanized trim as shown



### Gable End Stud Detail (2 Required)




### End Stud Detail (4 Required)




### Rafters

Cut 14 rafters 6' 6 9/16" long from 2" x 4"s and nail to ridge beam blocks and ceiling joists




### Ridge Beam Detail








### Ceiling Joists

Toenail seven 2" x 4" x 10' joists along side wall top plates with 10d nails



Toenail all rafters through top of rafter into ridge beam with one 20d nail



- A. Rear Wall Framing
- B. Front Wall Framing
- C. Side Wall Framing
- D. Floor Decking
- E. Corner Post Assembly and Top View

